
TECHNICAL SHEET


LEADER PF1CLASSIC















TECHNICAL FEATURES

LEADER PF 1 CLASSIC ECOMIX

| ENGINE STAGE V | | 1.12 | 1.14 | 1.16 |
|-----------------------|-------|------------------|------------------|------------------|
| Builder | | Deutz TCD 3,6 L4 | Deutz TCD 3,6 L4 | Deutz TCD 3,6 L4 |
| Power | kW/hp | 105/140 | 105/140 | 105/140 |
| Aftertreatment system | | DOC/DPF+SCR | DOC / DPF + SCR | DOC / DPF + SCR |
| Capacity | m³ | 12 | 14 | 16 |

| DIMENSIONS ECOMIX | | 1.12 | 1.14 | 1.16 |
|--------------------------|----|--------------|--------------|--------------|
| [A] total length | mm | 8010 | 7940 | 7440 |
| [B] height | mm | 2525 | 2780 | 3010 |
| [C] width | mm | 2550 | 2550 | 2550 |
| [D] milling cutter width | mm | 2040 | 2040 | 2040 |
| [E] milling height | mm | 4945 | 4945 | 4945 |
| [F] unloading height | mm | 375 | 375 | 395 |
| [G] outside wheels | mm | 2165 | 2165 | 2235 |
| [H] axle clearance | mm | 3860 | 3860 | 3860 |
| [I] rear projection | mm | 1000 | 1000 | 1000 |
| [L] front projection | mm | 3150 | 3080 | 2580 |
| [M] frame height | mm | 325 | 325 | 345 |
| WEIGHT | | | | |
| Unladen weight | kg | 11200 | 11450 | 11850 |
| TYRES | | | | |
| Standard front | | 315/60 R22.5 | 315/60 R22.5 | 315/60 R22.5 |
| Standard rear | | 285/70 R19,5 | 285/70 R19,5 | 285/70 R19,5 |

| CONFIGURATION | ECOMIX | |
|---------------------------------------------------------------------------|--------------------------------------|-------------------------------------|
| Number of knives | from 10 to 14 | |
| Adjustable seat with air suspension | • | |
| Joystick | multi-function electro-proportional | |
| Cabin | PF Cab | |
| Ventilation system | three speeds and temperature setting | |
| 6 Work led lights | • | |
| Fuel tank | I | 230 |
| Electronic weighing system with four sensors between mixing tub and frame | | • |
| Maximum speed | km/h | 27 |
| Frontaxle | | drive, steering and with suspension |
| Rear axle | | fixed (steering option) |
| Abs system | | - |
| Asr system | | - |
| Number of augers | | 1 |
| Speed range of the auger | rpm | 5, 10, 15, 20, 25, 30, 40 |
| External diameter of milling cutter roller | mm | 600 |
| Manual counter-knives | | 2 |
| Shredder on milling cutter | | - |
| Automatic greasing system | | 0 |
| | | |

● Standard Optional - Not available